

PRESCOT

OPRAWY LED

AMONA





AMONA



AMONA



NR KATALOGOWY	MOC [W]	BARWA [K]	JASNOŚĆ [lm]	NAPIĘCIE [V]	Ra	DIODA	OBUDOWA	OCHRONA	WYMIAR [mm]	EAN
OP-AMONA-59-WW	59	3000	10100	220-240	80	SMD3030	PC UV	IP66	1180x85x75	5903684855483
OP-AMONA-59-NW	59	4000	10100	220-240	80	SMD3030	PC UV	IP66	1180x85x75	5901885268576
OP-AMONA-59-W	59	6000	10100	220-240	80	SMD3030	PC UV	IP66	1180x85x75	5903684855490
OP-AMONA-69-WW	69	3000	10100	220-240	80	SMD3030	PC UV	IP66	1180x85x75	5903684855506
OP-AMONA-69-NW	69	4000	10100	220-240	80	SMD3030	PC UV	IP66	1180x85x75	5903684855513
OP-AMONA-69-W	69	6000	10100	220-240	80	SMD3030	PC UV	IP66	1180x85x75	5903684855520

INFORMACJA DODATKOWA

Możemy wyprodukować oprawę o dowolnych parametrach w oparciu o zapotrzebowanie klienta.

Dostępne modele z Dali, 1-10V, Triac, Awaryjne.

PRESCOT LED

PRESCOT Sp. z o.o.

ul. Wileńska 1, 11-500 Giżycko

Telefon: +48 87 428 21 18

Fax: +48 87 428 17 09

komponenty@prescot.pl

www.prescot.pl